

DLA-VS47NV

Laser-Phosphor Illumination
with **a dedicated IR LED engine**
for Stimulated NVG Exercises

8K e-shift
17.7 MP Effective Resolution

120 Hz Frame Rate

Digital Smear Reduction
with Black Frame Insertion

15,000:1 Contrast Ratio



*Shown with optional lens

D-ILA[®]

8K
e-shift

BLU⁺Escent

Features

- Laser-Phosphor Illumination System with Long Life for Low Operating Cost and Consistent Performance
- New dedicated IR-LED Light Engine for Stimulated NVG
- 3 Active Matrix, 0.69-inch Digital D-ILA Devices
- 4096 x 2160 Native Resolution (8192 x 4320 addressable 8K e-shift mode)
- 3,000 lumens (typical)
- Sequential Contrast Ratio 15,000:1 (typical)
- 12-bit Color Bit Depth via DisplayPort 1.2a Inputs
- 6-axis Color Management System w/12-bit Gamma Correction
- Color Gamut—Default Calibration sRGB / Rec. 709
- Improved Digital Smear Reduction w/120Hz Laser Pulse Control
- Low-latency Signal Processing
- 50 Hz, 60 Hz, 120 Hz Synchronous Operation
- Comprehensive LAN/RS-232-C Control Protocol
- 100%–25% Illumination Control (125 steps)
- Built-in Auto Intensity and Color Calibration for Reduced Maintenance
- Frame-Encoded Dynamic Laser Control (FEDLC)
- User Adjustable Gamma Presets
- Long-life Wiregrid Polarizers and Inorganic Optical Components
- Zoom and Dual Cove Lens Options Available
- Custom Fixed and Adjustable Lens Mount Options Available
- Flexible Orientation - Unlimited Pitch and Roll
- 11 x 11 Matrix, 1/16 pixel Micro-convergence Control
- Easy Access Front Panel for Lens/Mount Access
- USB Firmware Upgrade and Configuration Save/Restore Capability
- Motion Compatible for Simulation Applications

Specifications

Model	DLA-VS47NV	
Image device	0.69-inch D-ILA (4096 × 2160 pixels) ×3	
Brightness	3,000 ANSI lumens (typical) / 2,400 ANSI lumens (minimum)	
Resolution	4096 × 2160 (8192 × 4320 addressable in e-shift mode)	
Contrast ratio (sequential)	Visible: 15,000:1 (typical) IR: 13,000:1 (typical)	
Uniformity	Greater than 78%	
Aperture	8 steps (light aperture)	
Gamma control	Standard 2.2 gamma and 3 user adjustable gamma presets	
Color management	6-axis adjustable Color management system	
Input-supported formats	4096×2160, 3840×2160, 2560×1600, 2048×1536, 1920×1200, 1600×1200, 2048×1080, 1920×1080, 640×480 50 Hz, 60 Hz, 120 Hz Single, Dual stripe, Quad stripe, Quad cross input modes	
Latency	<16.6 ms w/120 Hz input, <25 ms w/60 Hz, <30 ms w/50 Hz input	
Clear Motion Drive (CMD)	Off, Mode 1–3. Available at 120, 60, and 50 Hz	
Color bit depth	12-bit input, 12-bit display	
I/O terminals	DisplayPort 1.2a ×4, Sync out (mini jack TTL output) ×1, RS-232-C (D-sub 9-pin male) ×1, LAN terminal (RJ-45 jack) ×1, Remote terminal (stereo mini jack) ×1, USB port (Type A) ×1	
Remote control	RS-232-C/LAN fully featured control protocol, Wired/IR remote control	
Light source	Blu-Escent Laser/Phosphor: 125-step power setting (25%–100%) IR LED: 125-step IR LED current setting (25%–100%)	
IR LED wavelength	750 nm	
Light source life	Average 20,000 h at 100% output (depending on the environment)	
Screen size	Approx. 60–300 inches (aspect ratio of 4096 × 2160)	
Power requirement	100–240 VAC, 50/60 Hz	
Power consumption	750 watts, 1.5 watts in standby mode	
Calorific value	2,700 kJ/h (648 kcal/h)	
Noise level (0°C to 26°C)	<49 dB(A) at 1 m (3.3 ft)	
Operating environment	Temperature: 5°C to 35°C Humidity: 20% to 80% (non-condensing)	
Storage temperature	–10°C to 60°C	
Operating altitude	<2,000 meters for safe operation	
Installation orientation	Angle free	
Motion platform	Motion compliant	
Dimensions (W × H × D)	500 × 235 × 741 mm with feet, 500 × 215 × 741 mm without feet	
Weight	Approx. 35 kg	
Supplied accessories	Power cord ×2 (US, EU), Remote control, Lens spacer	
Approvals	Safety	North America: CSA C22.2 No.60950-1-07, UL60950-1, 2 nd Europe: IEC60950-1:2005/A1:2009/A2:2013, EN60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013 China: GB4943.1-2011
	Safety (Laser)	North America: IEC60825-1: 2007(2nd edition) The other countries: IEC60825-1: 2014(3rd edition)
	EMC	North America: FCC part 15 subpart B Class A(US), ICES-003 Issue 6 Class A(CAN) Europe: EN61000-3-2, EN61000-3-3, EN55032 (Class A), EN55024 Australia: AS/NZS: CISPR32 Class A China: GB9254-2008, GB17625.1-2012
	Environmental	RoHS North America Proposition 65 (US) Europe WEEE New Battery directive, REACH
Optional product	Calibration Software: PK-CS1601W	
	Short throw zoom lens: GL-MZ4009SZW TR: 0.94–1.30:1, ±50% Vertical offset, ±18% Horizontal offset capability	
	Standard zoom lens: GL-MZ4014SZW TR: 1.27–2.54:1, ±100% Vertical offset, ±40% Horizontal offset Capability	
	Dual cove lens: VSL40FE Motorized lens shift mount: PK-MLS01W	

Options



GL-MZ4009SZW

0.94–1.3:1 Zoom Lens




GL-MZ4014SZW

1.27–2.54:1 Zoom Lens




VSL40FE

Dual Cove Lens



PK-MLS01W

Motorized Lens Shift Mount



PK-CS1601W

Calibration Software

Design and specifications are subject to change without notice. All pictures on this brochure are simulated. Please be aware that, because the D-ILA device is manufactured using highly advanced technologies, 0.01% or fewer of the pixels may be non-performing (always on or off). This product is designed for professional use; operator of the product must be a trained professional.

D-ILA and BLU-Escent are registered trademarks of JVCKENWOOD Corporation. All other brands and product names in this brochure may be trademarks and/or registered trademarks of their respective owners. Any rights not expressly granted herein are reserved.

Copyright © 2018, JVCKENWOOD Corporation. All Rights Reserved.

eu.jvc.com/pro/projectors/

